# An Optimal Real-Time Voltage and Frequency Scaling for Uniform Multiprocessors

Software Engineering Institute Carnegie Mellon University Pittsburgh, PA 15213

Gabriel Moreno Dionisio de Niz

August, 2012

a. REPORT unclassified	b. ABSTRACT <b>unclassified</b>	c. THIS PAGE unclassified	Same as Report (SAR)	29	
16. SECURITY CLASSIFIC		17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON	
15. SUBJECT TERMS					
14. ABSTRACT					
=	OTES CEE International Coul, Korea on 20-22		edded and Real-Ti	me Computi	ng Systems and
Approved for public release; distribution unlimited					
12. DISTRIBUTION/AVAILABILITY STATEMENT				NUMBER(S)	
				11. SPONSOR/MONITOR'S REPORT	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)				10. SPONSOR/MONITOR'S ACRONYM(S)	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  Carnegie Mellon University,Software Engineering Institute,Pittsburgh,PA,15213				8. PERFORMING ORGANIZATION REPORT NUMBER	
				5f. WORK UNIT NUMBER	
				5e. TASK NUMBER	
4. TITLE AND SUBTITLE  An Optimal Real-Time Voltage and Frequency Scaling for Uniform  Multiprocessors  6. AUTHOR(S)				5d. PROJECT NUMBER	
				5c. PROGRAM ELEMENT NUMBER	
				5a. CONTRACT NUMBER  5b. GRANT NUMBER	
1. REPORT DATE AUG 2012	A DEPORT TYPE			3. DATES COVERED <b>00-00-2012</b> to <b>00-00-2012</b>	
maintaining the data needed, and c including suggestions for reducing	lection of information is estimated to completing and reviewing the collective this burden, to Washington Headquuld be aware that notwithstanding and DMB control number.	ion of information. Send comment arters Services, Directorate for Inf	s regarding this burden estimate of formation Operations and Reports	or any other aspect of the control o	his collection of information, Highway, Suite 1204, Arlington

**Report Documentation Page** 

Form Approved OMB No. 0704-0188 Copyright 2012 Carnegie Mellon University.

This material is based upon work supported by the Department of Defense under Contract No. FA8721-05-C-0003 with Carnegie Mellon University for the operation of the Software Engineering Institute, a federally funded research and development center.

Any opinions, findings and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the United States Department of Defense.

#### NO WARRANTY

THIS CARNEGIE MELLON UNIVERSITY AND SOFTWARE ENGINEERING INSTITUTE MATERIAL IS FURNISHED ON AN "AS-IS" BASIS. CARNEGIE MELLON UNIVERSITY MAKES NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, AS TO ANY MATTER INCLUDING, BUT NOT LIMITED TO, WARRANTY OF FITNESS FOR PURPOSE OR MERCHANTABILITY, EXCLUSIVITY, OR RESULTS OBTAINED FROM USE OF THE MATERIAL. CARNEGIE MELLON UNIVERSITY DOES NOT MAKE ANY WARRANTY OF ANY KIND WITH RESPECT TO FREEDOM FROM PATENT, TRADEMARK, OR COPYRIGHT INFRINGEMENT.

This material has been approved for public release and unlimited distribution except as restricted below.

Internal use:\* Permission to reproduce this material and to prepare derivative works from this material for internal use is granted, provided the copyright and "No Warranty" statements are included with all reproductions and derivative works.

External use:\* This material may be reproduced in its entirety, without modification, and freely distributed in written or electronic form without requesting formal permission. Permission is required for any other external and/or commercial use. Requests for permission should be directed to the Software Engineering Institute at <a href="mailto:permission@sei.cmu.edu">permission@sei.cmu.edu</a>.

\*These restrictions do not apply to U.S. government entities.

#### **Motivation**

Chip multiprocessors are the way to deal with increasing computational load in embedded real-time systems

 Power consumption, heat dissipation, and other physical constraints render single processors impractical



Power consumption is a concern in batterypowered real-time systems

- battery life time
- battery weight



#### **Overview**


Voltage and frequency scaling (VFS) allows reducing the power consumption of a processor, and its speed.

VFS in real-time systems must ensure that the system remains schedulable.

Existing VFS algorithms for multiprocessors leave unused idle capacity.

processor constraints

algorithm constraints



Growing Minimum Frequency (GMF) algorithm achieves better power efficiency.

- removes algorithm constraint
- reduces impact of processor constraints

### **Problem Description**

#### Given:

- multiprocessor platform supporting independent VFS, and
- a set of periodic tasks with implicit deadlines

#### Compute:

 frequency assignment that minimizes power consumption while meeting tasks' deadlines

### **Processor Power-Frequency Relationship**


Dynamic power in processors is proportional to the product of the processor frequency and the square of the supply voltage.

$$P \propto V^2 f$$

In VFS, power can be reduced by reducing the frequency, which allows a corresponding reduction in the voltage.

Since voltage is proportional to the frequency we can approximate as

$$P \propto f^3$$



#### **Task and Platform Model**

#### **Tasks**

```
n: number of tasks C_i: execution time of task \tau_i, measured at the highest frequency T_i: period of task \tau_i D_i = T_i: implicit deadlines u_i = \frac{C_i}{T_i}: utilization of task \tau_i U = \sum_{i=1}^n u_i: total utilization
```


#### Platform:

```
m: number of processors (all identical)
```

 $f_i$ : normalized frequency (1 = highest frequency) for processor i

## **Uniform Frequency Scaling**

- All processors assigned the same frequency
- Tasks scheduled with an optimal global scheduler (e.g., LNREF)



# Non-Uniform Frequency Scaling 1


Processor frequencies are assigned independently

Decide Independent Frequency algorithm avoids heavy task bottleneck [Funaoka 2008]

- Task  $\tau_i$  is heavy if its utilization would drive up the uniform frequency assignment for the remaining processors, i.e.  $u_i > \frac{\sum_{j=i}^n u_j}{m-i+1}$
- Each heavy task is assigned its own processor
- Remaining light tasks globally scheduled in remaining processors with uniform frequency assignment

## Non-Uniform Frequency Scaling 2

Decide Independent Frequency is optimal if frequency can be scaled continuously (i.e. to any frequency in a range)




### **Discrete Frequency Steps**

However, processors support a limited number of frequencies.

- DIF is not optimal in that setting
- Computing the optimal partition of processors and the frequency assignment is NP-Hard

Example: supported frequencies: 1, .75, .5



### **Achieving Better Power Efficiency**

#### Two problems

- Discrete frequency steps force leaving idle capacity in processor partitions
- Unused capacity in a processor partition cannot be used by tasks assigned to other partitions

**Observation:** if we can optimally schedule tasks allowing them to migrate between processors running at different frequencies we can do better

- avoid the set partition problem (and its computational complexity)
- achieve better power efficiency
  - no fragmentation of platform capacity
  - capacity left by heavy tasks is not wasted

#### **U-LLREF**

U-LLREF [Funk 2010] is an optimal global scheduling algorithm for uniform multiprocessors

- an extension of LLREF (a DP-fair algorithm)
- processors can run at different frequencies

A task set is schedulable by U-LLREF on a platform if the following holds

$$\sum_{i=1}^{k} u_i \le \sum_{i=1}^{k} f_i \qquad \forall k \in \{1, \dots, m-1\}$$

$$\sum_{i=1}^{n} u_i \le \sum_{i=1}^{m} f_i$$


where  $u_1 \geq \cdots \geq u_n$  and  $f_1 \geq \cdots \geq f_m$ 


## **Growing Minimum Frequency Algorithm**


**Overview:** satisfy each condition of the U-LLREF test using the most power efficient assignment of frequencies (lowest possible and distributed as uniformly as possible)


```
assign the lowest frequency to all the processors
for k = 1 to m do
    while k<sup>th</sup> U-LLREF condition not satisfied do
    increase the frequency of the slowest
        processors in subset 1..k to the next
        frequency step
    end while
end for
```

$$k = 1$$












$$k = 1$$













$$k = 1$$













$$k = 2$$











$$k = 2$$







**Carnegie Mellon** 


Key


task




$$k = 2$$












$$k = 3$$











$$k = 4 = m$$










$$\sum_{i=1}^{n} u_i = 3.1 > \sum_{i=1}^{m} f_i = 3.0$$

$$k = 4 = m$$








Key

In this case, frequency assignment is the same as in the Exhaustive partition search.





#### **Evaluation**

#### Randomly generated 15,000 tasksets


- utilization level ranging from 0.5 to 4 in steps of 0.25
- 1,000 tasksets for each utilization level
- each taskset composed of tasks with random uniform utilization

Used frequencies and voltages of three different quad-core processors

Computed frequency assignment and corresponding power with different multiprocessor VFS algorithms

- Decide Independent Frequency [Funaoka 2008]
- Exhaustive partition/frequency assignment search
- GMF
- Optimal (exhaustive frequency assignment w/o partitions)

#### **Evaluation Results**




### Optimality 1

GMF is optimal when the supported frequency steps are uniform.


#### **Proof** intuition:

- Any frequency step we choose is the same in terms of speed
- Increasing the frequency of the slowest processor requires the smallest power increase
- The optimal frequency assignment for the first *i* conditions bounds from below the optimal assignment for the *i*+1 conditions
- GMF assigns frequencies as even as possible within that bound



## Optimality 2

With non-uniform frequency steps, GMF may not optimal



We have observed that for some platforms with non-uniform frequency steps GMF is still optimal

• When the power steps associated frequency steps are non-decreasing

#### Conclusion

Growing Minimum Frequency (GMF) algorithm computes the optimal frequency assignment to minimize the power consumption of a real-time periodic taskset in a multiprocessor platform.

Evaluation results show up to 30% improvement over previous algorithms.

Avoiding partitioning allows GMF to achieve better power efficiency than optimal partitioned approaches.